

### Amendments to the Claims

Please amend the claims without prejudice. The listing of claims will replace all prior versions, and listings, of claims in the application:

### Listing of the Claims

- 1 (Currently amended) A borehole tool, comprising: a tool body; a series of arms connected to the tool body and moveable radially relative thereto; and a series of pads mounted on the arms so as to be pivotable relative thereto; ~~characterised in that~~ wherein the pads are pivotable about a radial axis relative to the tool body, and the pads are elongate pads adjacently arranged to provide different circumferential coverage according to the orientation with respect to the longitudinal axis of the borehole.
- 2 (Currently amended) A tool as claimed in claim 1, wherein the pads are connected to the arms such that the orientation of the pads relative to the tool body is determined by the extent of the arms in the radial direction.
- 3 (Currently amended) A tool as claimed in claim 1 ~~and~~ 2, wherein the pivoting of pads is synchronised such that the pads adopt a substantially regular pattern of orientation.
- 4 (Original) A tool as claimed in claim 3, wherein adjacent pads are interconnected so as to synchronise pivoting.
- 5 (Currently amended) A tool as claimed in ~~any preceding~~ claim 1, wherein the pads are arranged in a ring, each pad being connected at its ends to the adjacent pads.
- 6 (Currently amended) A tool as claimed in ~~any preceding~~ claim 1, wherein the arms are arranged symmetrically around the tool body.
- 7 (Currently amended) A tool as claimed in ~~any preceding~~ claim 1, wherein each arm is connected to the tool body at one end by a pivot or hinge that allows the arm to move in a radial plane relative to the tool body.
- 8 (Currently amended) A tool as claimed in ~~any preceding~~ claim 1, wherein the ends of the arms are be connected to the pads.

- 9 (Currently amended) A tool as claimed in ~~any preceding~~ claim 1, wherein the arms can move between two limit positions: the first in which the arm lies substantially parallel to the tool body; and the second in which the arm projects away from the tool body in a radial direction to contact the borehole wall.
- 10 (Currently amended) A tool as claimed in ~~any preceding~~ claim 1, wherein the series of arms comprises two sets of arms separated along the tool body with the series of pads encircling the body between the sets of arms.
- 11 (Original) A tool as claimed in claim 10, wherein the arms of each set extend from the connection on the tool body towards the other set.
- 12 (Original) A tool as claimed in claim 11, wherein the two sets of arms are arranged on the tool body in an angularly offset configuration.
- 13 (Original) A tool as claimed in claim 12, wherein the pads are connected to the arms in such a way that one end of a pad is connected to an arm from the first set and the other end of the pad is connected to the adjacent arm of the second set.
- 14 (Currently amended) A tool as claimed in ~~any preceding~~ claim 1, wherein the pads form a zigzag array extending around the circumference of the borehole.
- 15 (Original) A tool as claimed in claim 14, wherein each arm is connected to two pads at adjacent ends.
- 16 (Currently amended) A tool as claimed in ~~any of~~ claims 10-13, wherein the ends of one set of arms are located in a fixed position on the tool body and the ends of the other set are located on the tool body by means of a sliding ring which can be driven along the tool body to cause the arms of both sets to extend or retract.
- 17 (Original) A tool as claimed in claim 16, further comprising a detector for detecting the angle between any arm and the tool axis.
- 18 (Currently amended) A tool as claimed in claim 16 ~~or 17~~, wherein the location of the arms on the ring is provided so as to allow axial movement of the ends of the arms relative to the tool body.

- 19 (Original) A tool as claimed in claim 18, further comprising a detector for detecting the axial position of the ring and the location point of each arm.
- 20 (Currently amended) The use of a tool as claimed in ~~any of~~ claims 17, ~~18-19~~ to determine the size of a borehole in which it is positioned.
- 21 (Currently amended) The use of a tool as claimed in claim 18 ~~or 19~~ to determining the shape of a hole in which it is positioned.
- 22 (New) A tool as claimed in claim 17, wherein the location of the arms on the ring is provided so as to allow axial movement of the ends of the arms relative to the tool body.
- 23 (New) The use of a tool as claimed in claims 22 to determine the size of a borehole in which it is positioned.